



Bitutainer Specifications

Suitable for storage and multi-modal transportation of bitumen, bitumen emulsions, polymer modified bitumen's, waste oils and heavy fuel oils

A unique concept in bitumen distribution with 30% more carrying capacity than conventional tank containers

- Water capacity 29,000 liters
- Transported as a standard 20ft ISO tank container
- ISO 1496 Part 3 – Type 75 – “Tank Containers”
- Ideal for sea, road and rail transportation
- Design allows partial payloads to be carried (baffled)
- High performance heating systems (8-10°C/hour) via heating tubes (flu pipes)
- High value factory installed insulation with robust outer skin

Optional accessories and auxiliary items:

- Quick fit diesel burners
- Flame/flu pipe liners
- Flexi hoses
- Specialized bitumen pumps

Ratings:

Max Gross Weight	35,000 Kgs
Payload	29,000 Kgs
Tare Weight	<6,000 Kgs

Measures:

Length	6058 mm (20')
Width	2438 mm (8')
Height	2591 mm (8'6")



The Quarterdeck, Level 1, 69 Richefond Circle, Ridgeside Office Park, Umhlanga 4321, South Africa. | Private Bag X011, Umhlanga 4320.
Tel: +27 31 561 6767 | Website: www.almarcontainergroup.com | Reg. No: 1997/002063/07

Chairman: JA Forbes
Directors: FD Du Plessis ZB Aszalos